




SHIMPO RK-3E

SHIMPO RK-3E pottery wheel uses an exceptional Direct Drive motor. The Direct Drive motor is a brushless, beltless motor that operates on a magnet system and is electronically controlled. As a result, the motor is **EXTREMELY** quiet!

Features

- › Direct drive system; DC brushless motor
- › 355.6 mm wheel-head
- › Wheel-head Direction; clockwise/Counter-clockwise
- › Adjustable legs
- › Legs can be removed for storage or tabletop use
- › Virtually quiet; no belts, no vibration
- › Wheel-head acts as a banding wheel when the pedal is at stop
- › Pedal stops the wheel head immediately; no belt means no extra rotation when stopped
- › Higher torque; no belts
- › Maintains a specific set speed when stepping away to center, even with slow speeds with 45.3592 mm of clay



Optional Accessory:
SHIMPO RK-3E extension legs to throw standing. The legs are made from heavy gauge, powder coated steel and designed with a curve for extreme stability. The legs will raise the SHIMPO RK-3E to a height of 889 mm to 939 mm in 25.4 mm increments.



SHIMPO RK-3E
Extension Legs

Wheel Weight	54 kg
Wheel Dimensions	587.375 mm x 698.5 mm x 857.25 mm
Adjustable Leg Height	457.2 mm - 533.4 mm (25.4 mm increments)
Centering	45 kg